

COM

9/29 14:30

r 6001

m

ED RADIO SYSTE PSO3H IP503H Lite

IP TRANSCEIVER

You Can Talk and Listen at the Same Time Full-Duplex IP Radio





- Multiple User Communication Multiple users in the call groups can initiate calls instantaneously.
- **Priority Interrupt Calling** You can break into an on-going call to transmit an important message.
- Industry Leading Compact and Lightweight Design
- IP67 Dust-Tight and Waterproof
- 900 mW Powerful and Clear Audio

Other Features

- Individual, Group, Talkgroup, Multiplex Talkgroup and All calls*
 * Depending on system configuration
- Emergency button, Lone Worker and Man Down functions
- Vibration alert function notifies of incoming call
- Up to 500 memory address book
- (including Group, Individual, Talkgroup and Telephone lists)
- Voice message recording
- Built-in Bluetooth[®] capability

IP503H Lite



AUS	LTE B1, B3, B5, B7, B8, B28 W-CDMA B1, B5
s not included)	$59 \times 95 \times 32$ mm; $2.3 \times 3.7 \times 1.3$ in (with BP-272)
	240 g; 8.5 oz (with BP-272 and antenna)
	G.726 (32 kbps)
AF output power Internal SP (8 Ω at 10% distortion) External SP	More than 900 mW
External SP	More than 200 mW
andby = 5 : 5 : 90)	17 hours (with BP-272)
	Ver 2.1 +EDR
	Built-in
re	-10 °C to +60 °C; +14 °F to +140 °F
	IP67 (dust-tight and waterproof) IP55/54 (dust and water jet / water resistance)

Operating time may differ depending on operating environment. All stated specifications are subject to change without notice or obligation

Note for IP503H users:

The IP503H Lite (front panel is blue) uses a generally available data SIM card and is controlled by the IP4000C system.

The IP503H Lite is not compatible with IP503H radios (black front panel) which use a closed network provided by custom Icom SIM card.



500.5

501.5

502.5

503.5

505.5

506.5

510.5 512.5

514.6

516.6

Also meets equivalent MIL-STD-810-C, -D, -E and -F.

Antenna

I, II

I, II

I, II

I-C

I

I. III

I IV

MB-135 belt clip

Please ask your lcom distributor in your country about the planned launch date of the service or other requirements. This product requires radio registration at lcom Inc. lcom, lcom Inc. and the lcom logo are registered trademarks of lcom Incorporated (Japan) in Japan, the United States, the United Kingdom, Germany, France, Spain, Russia, Australia, New Zealand, and/or other countries. The Bluetooth® word mark and logos are registered trademark owned by Bluetooth SIG, Inc. and any use of such marks by lcom Inc. is under license. All other trademarks are the properties of their respective holders.

Icom America Inc. www.icomamerica.com

Icom Canada www.icomcanada.com

Icom Brazil E-mail: sales@icombrazil.com

> Icom France s.a.s. www.icom-france.com

ICOM Inc. 1-1-32, Kamiminami, Hirano-Ku, Osaka 547-0003, Japan Phone: +81 (06) 6793 5302 Fax: +81 (06) 6793 0013

Icom (Europe) GmbH

www.icomeurope.com

Icom Spain S.L.

www.icomspain.com

Icom (UK) Ltd.

www.icomuk.co.uk

Icom (Australia) Pty. Ltd. www.icom.net.au

Icom Asia Co., Ltd. www.icomasia.com

Shanghai Icom Ltd. www.bjicom.com

VE-SP1

JUST SLOT IN THE IP503H Lite AND START A VOICE CONFERENCE

- Portable operation with LR6 (AA)×8 cells Built-in loudspeaker and high sensitivity
- microphone Charges the radio while using with the AC adapter · Great as a teleworking type solution
- * The transceiver is not supplied

www.icomjapan.com

Low Pressure

High Temperature

Low Temperature

Solar Radiation

Dust Blowing

Immersion Vibration

Hand strap

Shock

Rain Blowing/Drip

Supplied accessories

BP-272 Li-ion battery pack

Temperature Shock

Count on us!

Your local distributor/dealer:

A4 20FGG514A © 2020 Icom Inc.